

MOBILE ACCESS PLATFORM



The Mobile Access Platform is designed to provide portable access for workers on tank trucks or railcars. The system features lightweight aircraft aluminum construction, a rugged winch, and zinc-plated steel hardware for maximum corrosion resistance. Customize the unit for your purposes by choosing a platform size, wheel kit, and other fall-arrest/ safety options.



MOBILE ACCESS PLATFORM

The **Mobile Access Platform** provides access to elevated work areas with fall-protection.

FEATURES

- Designed to position workers over tank manways
- Lightweight aircraft aluminum construction
- Rugged winch easily adjusts ladder height
- Zinc-plated steel hardware for maximum corrosion resistance
- Ladder adjusts with 5ft (1.5 m) of travel
- Customizable to suit your specific application needs

CUSTOM DESIGNS

Available in a range of heights and wheel styles, the system can be ordered to meet your applications' custom requirements.

OSHA COMPLIANT

The Mobile Access Platform meets the applicable requirements of the standards set out by the following:

- 1) ANSI 14.3 Requirement for fixed ladders
- 2) OSHA 1910.26 Portable metal ladders
- 3) CSAZ11-M81 Portable ladders
- 4) OSHA 1910.23 Guarding floor/wall openings & holes
- 5) Manitoba Workplace Safety & Health Division Fall Protection Guidelines

WHY FLS?

Maximizing the fall-safety provided by the Mobile Access Platform requires the proper harnesses, lanyards, and training. **FLS is your turnkey fall-protection provider.** Piecemeal competitors can't compare with FLS' turnkey costs and services.



Guard Rail Cage

5.5 ft. Diameter Guard Rail Cage

- Two (2) Non-Adjustable Outriggers 198516044 or
- Two (2) Adjustable Outriggers 198517944
- Fall Out Bar** fills gaps under guard rail cage (4 required.) 198516269

Nonslip rubber footpad

Fall Arrest Option

- 54" Platform Assembly** 198515084
- Fall Arrest Tie-Off Post** 198515551
- Platform Corner w/o Sleeve** 2 X 198515085

Tie-off post

Fold up mast

Corner sleeve

Upper Platform Handrails 198516138

Adjustable Platform

- 28" to 42" Adjustable Platform** Ideal for simple maintenance and recommended for use with guard rail cage 198515126

Standard Sizes by Platform Height

P = Pneumatic U = Urethane

- 21.4' Height*** 16.6' minimum 198517296 (P) 198517295 (U)
- 19.5' Height*** 14.7' minimum 198517294 (P) 198517293 (U)
- 17.5' Height*** 12.7' minimum 198517292 (P) 198517291 (U)
- 15.5' Height*** 10.8' minimum 198517290 (P) 198517289 (U)
- 14.6' Height*** 9.8' minimum 198517288 (P) 198517287 (U)
- 13.6' Height*** 8.8' minimum 198517286 (P) 198517285 (U)

Optional Tow Bar Package

- Tow Bar Package 198516082
- Pintle Hitch 198516187
- 2" Ball Adaptor 198513572

Fall Arrest & Confined Space Entry Option

- 54" Platform Assembly** 198515084
- Fall Arrest Tie-Off Post** 198515551
- Platform Corner w/o Sleeve** 198515085
- Platform Corner w/ Sleeve** 198515086
- Fold up Mast** 198511851

Base Mounted Counterweight Bars Additional counterweight bars can be added to help balance your Ladder Access System when using various guardrails and platforms 198517070

15" Top-Wind Jacks Each has a capacity of 5000 lbs 198519536

Side Moving Wheel Kit for sideways movement and easy repositioning 198515349

18" Pneumatic Wheels for outside use, asphalt surfaces, and long distances

8" Urethane Wheels* for indoor use, clean areas, or painted floors

*Listed platform height measurements reduced 10 inches when using urethane wheels